

Description

length: 2", thread: 10-32, cadmium plated steel philips recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN5261032R32
Minimum Qty (MOQ):	25
NSN:	5305-00-150-9404

NO IMAGE
AVAILABLE

P/N AN526-1032R32 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.938 Inches Minimum And 2.000 Inches Maximum
Fastener Length:	1.938 Inches Minimum And 2.000 Inches Maximum
Head Style:	Button
Head Diameter:	0.425 Inches Minimum And 0.448 Inches Maximum
Head Height:	0.118 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Screw Material:	Steel
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	3 Type And 7c Style

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN526-1032R32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.