

Description

length: 5/16", thread: 10-32, cadmium plated steel philips recess"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN5261032R5
Minimum Qty (MOQ):	100
NSN:	5305-00-167-3930



\* See page 2 for technical characteristics

## P/N AN526-1032R5 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.281 Inches Minimum And 0.312 Inches Maximum
<b>Fastener Length:</b>	0.281 Inches Minimum And 0.312 Inches Maximum
<b>Head Style:</b>	Button
<b>Head Diameter:</b>	0.425 Inches Minimum And 0.448 Inches Maximum
<b>Head Height:</b>	0.118 Inches Nominal
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	55000 Pounds Per Square Inch
<b>Screw Material:</b>	Steel Comp 1010
<b>Screw Material Document And Classification:</b>	Qq-s-671 Fed Spec Single Material Response
<b>Screw Surface Treatment:</b>	Cadmium
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unf
<b>Nondefinitive Spec/std Data:</b>	3 Type And 7c Style

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN526-1032R5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.