

Description

length: 9/16", thread: 10-32, cadmium plated steel philips recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN5261032R9 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-00-151-2234 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N AN526-1032R9 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.500 Inches Minimum And 0.562 Inches Maximum |
| Fastener Length: | 0.562 Inches Nominal |
| Head Style: | Button |
| Head Diameter: | 0.425 Inches Minimum And 0.448 Inches Maximum |
| Head Height: | 0.118 Inches Maximum |
| Internal Drive Style: | Cross Recess Type Ii |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 55000 Pounds Per Square Inch |
| Screw Material: | Steel Or Steel Comp 1010 |
| Screw Material Document And Classification: | Qq-s-630 Fed Spec 2nd Material Response Or Qq-s-631 Fed Spec 2nd Material Response Or Qq-s-634 Fed Spec 2nd Material Response |
| Screw Surface Treatment: | Cadmium |
| Screw Surface Treatment Document And Classification: | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unf |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN526-1032R9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.