

Description

length: 7/8", thread: 6-32, cadmium plated steel, phillips recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

MS35206-233

SKU / Model:	AN526632R14
Minimum Qty (MOQ):	100
NSN:	5305-00-144-3919
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN526-632R14 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.844 Inches Minimum And 0.875 Inches Maximum
Fastener Length:	0.844 Inches Minimum And 0.875 Inches Maximum
Head Style:	Button
Head Diameter:	0.303 Inches Minimum And 0.321 Inches Maximum
Head Height:	0.086 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Screw Material:	Steel
Screw Surface Treatment:	Cadmium
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN526-632R14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.