

Description

length: 3/8", thread: 6-32, cadmium plated steel, philips recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN526632R6
Minimum Qty (MOQ):	100
NSN:	5305-00-144-3913
ECCN:	EAR99



P/N AN526-632R6 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Fastener Length:	0.375 Inches Nominal
Head Style:	Button
Head Diameter:	0.303 Inches Minimum And 0.321 Inches Maximum
Head Height:	0.086 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Screw Material:	Steel Or Steel Comp 1010
Screw Material Document And Classification:	Qq-s-630 Fed Spec 2nd Material Response Or Qq-s-631 Fed Spec 2nd Material Response Or Qq-s-634 Fed Spec 2nd Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN526-632R6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.