

Description

length: 1-1/2, thread: 8-32, cadmium plated steel - phillips recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN526832R24
Minimum Qty (MOQ):	100
NSN:	5305-00-151-0578
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN526-832R24 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.438 Inches Minimum And 1.500 Inches Maximum
Fastener Length:	1.438 Inches Minimum And 1.500 Inches Maximum
Head Style:	Button
Head Diameter:	0.364 Inches Minimum And 0.384 Inches Maximum
Head Height:	0.102 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Screw Material:	Steel
Screw Surface Treatment:	Cadmium
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	lii Type And 7c Style

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN526-832R24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.