

Description

length: 2", thread: 8-32, cadmium plated steel philips recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN526832R32 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5305-00-151-0574 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N AN526-832R32 Specifications

| | |
|----------------------------------|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.938 Inches Minimum And 2.000 Inches Maximum |
| Fastener Length: | 1.938 Inches Minimum And 2.000 Inches Maximum |
| Head Style: | Button |
| Head Diameter: | 0.364 Inches Minimum And 0.384 Inches Maximum |
| Head Height: | 0.102 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 55000 Pounds Per Square Inch |
| Screw Material: | Steel |
| Screw Surface Treatment: | Cadmium |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN526-832R32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.