

**Description**

length: 1/2", thread: 8-32, cadmium plated steel philips recess, AN526 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN526832R8
Minimum Qty (MOQ):	100
NSN:	5305-00-984-6193
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N AN526-832R8 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.438 Inches Minimum And 0.500 Inches Maximum
<b>Fastener Length:</b>	0.500 Inches Nominal
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.306 Inches Minimum And 0.322 Inches Maximum
<b>Head Height:</b>	0.105 Inches Minimum And 0.115 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>End Item Identification:</b>	Nsn 4210-01-486-1035 Tfft (tactical Fire Fighting Truck)
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	60000 Pounds Per Square Inch
<b>Screw Material:</b>	Steel Comp 1010 Or Steel Comp 1011 Or Steel Comp 1013
<b>Screw Material Document And Classification:</b>	66 Fed Std All Material Responses
<b>Screw Surface Treatment:</b>	Cadmium And Chromate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unc
<b>Nondefinitive Spec/std Data:</b>	3 Type And 9c Style

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN526-832R8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.