

**Description**

Length: 3/8", thread: 10-32, corrosion resistant steel, philips recess, truss head, AN526 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN526C1032R6
Minimum Qty (MOQ):	100
NSN:	5305-00-879-4866
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N AN526C1032R6 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.375 Inches Minimum
<b>Fastener Length:</b>	0.375 Inches Nominal
<b>Head Style:</b>	Button
<b>Head Diameter:</b>	0.425 Inches Minimum And 0.448 Inches Maximum
<b>Head Height:</b>	0.118 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	80000 Pounds Per Square Inch
<b>Screw Material:</b>	Steel Corrosion Resisting
<b>Screw Material Document And Classification:</b>	66 Fed Std Single Material Response
<b>Screw Surface Treatment:</b>	Passivate
<b>Thread Series Designator:</b>	Unf
<b>Nondefinitive Spec/std Data:</b>	3 Type And 7c Style

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN526C1032R6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.