

Description

Length: 3/8", thread: 10-32, corrosion resistant steel, philips recess, truss head, AN526 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN526C1032R6 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-00-879-4866 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N AN526C1032R6 Specifications

| | |
|--|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.375 Inches Minimum |
| Fastener Length: | 0.375 Inches Nominal |
| Head Style: | Button |
| Head Diameter: | 0.425 Inches Minimum And 0.448 Inches Maximum |
| Head Height: | 0.118 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 80000 Pounds Per Square Inch |
| Screw Material: | Steel Corrosion Resisting |
| Screw Material Document And Classification: | 66 Fed Std Single Material Response |
| Screw Surface Treatment: | Passivate |
| Thread Series Designator: | Unf |
| Nondefinitive Spec/std Data: | 3 Type And 7c Style |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN526C1032R6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.