

Description

Length: 3/8", thread: 10-32, corrosion resistant steel, philips recess, truss head, AN526 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN526C1032R6
Minimum Qty (MOQ):	100
NSN:	5305-00-879-4866
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN526C1032R6 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.375 Inches Minimum
Fastener Length:	0.375 Inches Nominal
Head Style:	Button
Head Diameter:	0.425 Inches Minimum And 0.448 Inches Maximum
Head Height:	0.118 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	66 Fed Std Single Material Response
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	3 Type And 7c Style

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN526C1032R6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.