

Description

Length: 9/16", thread: 10-32, corrosion resistant steel, philips recess, AN526 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN526C1032R9
Minimum Qty (MOQ):	100
NSN:	5305-00-403-0575
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N AN526C1032R9 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.469 Inches Minimum And 0.531 Inches Maximum
Fastener Length:	0.531 Inches Minimum And 0.562 Inches Maximum
Head Style:	Button
Head Diameter:	0.425 Inches Minimum And 0.448 Inches Maximum
Head Height:	0.118 Inches Nominal
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Screw Material:	Steel Comp 302 Or Steel Comp 430
Screw Material Document And Classification:	Mil-s-7720 Mil Spec 1st Material Response Or Qq-s-763 Fed Spec 2nd Material Response
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN526C1032R9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.