

Description

length: 5/8", thread: 6-32, corrosion resistant steel, philips recess, pan head

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | AN526C632R10 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-01-527-8141 |
| ECCN: | EAR99 |



P/N AN526C632R10 Specifications

| | |
|---|------------------------------|
| Thread Direction: | Right-hand |
| Thread Length: | 0.625 Inches Nominal |
| Fastener Length: | 0.625 Inches Nominal |
| Head Style: | Truss |
| Head Diameter: | 0.448 Inches Nominal |
| Head Height: | 0.118 Inches Nominal |
| Hole Diameter: | 0.190 Inches Nominal |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.188 Inches |
| Hole Quantity: | 2 |
| Nonstandard Thread Pitch Diameter: | +0.1073/+0.1109 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 55000 Pounds Per Square Inch |
| Screw Material: | Steel Corrosion Resisting |
| Screw Surface Treatment: | Passivate |
| Head Hole Configuration Style: | Double Hexagon Flats |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN526C632R10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.