

**Description**

length: 5/8", thread: 6-32, corrosion resistant steel, philips recess, pan head

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN526C632R10
Minimum Qty (MOQ):	100
NSN:	5305-01-527-8141
ECCN:	EAR99



## P/N AN526C632R10 Specifications

<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.625 Inches Nominal
<b>Fastener Length:</b>	0.625 Inches Nominal
<b>Head Style:</b>	Truss
<b>Head Diameter:</b>	0.448 Inches Nominal
<b>Head Height:</b>	0.118 Inches Nominal
<b>Hole Diameter:</b>	0.190 Inches Nominal
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.188 Inches
<b>Hole Quantity:</b>	2
<b>Nonstandard Thread Pitch Diameter:</b>	+0.1073/+0.1109 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	55000 Pounds Per Square Inch
<b>Screw Material:</b>	Steel Corrosion Resisting
<b>Screw Surface Treatment:</b>	Passivate
<b>Head Hole Configuration Style:</b>	Double Hexagon Flats
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN526C632R10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.