

Description

length: 5/8", thread: 6-32, corrosion resistant steel, philips recess, pan head

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[AN526C-632R10](#)

SKU / Model:	AN526C632R10
Minimum Qty (MOQ):	100
NSN:	5305-01-527-8141
ECCN:	EAR99



P/N AN526C632R10 Specifications

Thread Direction:	Right-hand
Thread Length:	0.625 Inches Nominal
Fastener Length:	0.625 Inches Nominal
Head Style:	Truss
Head Diameter:	0.448 Inches Nominal
Head Height:	0.118 Inches Nominal
Hole Diameter:	0.190 Inches Nominal
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.188 Inches
Hole Quantity:	2
Nonstandard Thread Pitch Diameter:	+0.1073/+0.1109 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Screw Material:	Steel Corrosion Resisting
Screw Surface Treatment:	Passivate
Head Hole Configuration Style:	Double Hexagon Flats
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN526C632R10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.