

P/N AN526C632R6

Description

length: 3/8", thread: 6-32, corrosion resistant steel, philips recess

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: AN526C632R6

Minimum Qty (MOQ): 100

NSN: 5305-00-812-9832

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N AN526C632R6 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.344 Inches Minimum And 0.375 Inches Maximum
Fastener Length:	0.344 Inches Minimum And 0.375 Inches Maximum
Head Style:	Button
Head Diameter:	0.303 Inches Minimum And 0.321 Inches Maximum
Head Height:	0.086 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Screw Material:	Steel Corrosion Resisting
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/AN526C632R6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/AN526C632R6 and selecting the quantity you