

**Description**


length: 9/16", thread: 8-32, corrosion resistant steel, philips recess

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN526C832R9
Minimum Qty (MOQ):	100
NSN:	5305-00-637-7437
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N AN526C832R9 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.531 Inches Minimum And 0.562 Inches Maximum
<b>Fastener Length:</b>	0.531 Inches Minimum And 0.562 Inches Maximum
<b>Head Style:</b>	Button
<b>Head Diameter:</b>	0.364 Inches Minimum And 0.384 Inches Maximum
<b>Head Height:</b>	0.102 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Screw Material:</b>	Steel Corrosion Resisting
<b>Screw Surface Treatment:</b>	Passivate
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN526C832R9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.