

# P/N AN526DD632-5

### **Description**

Fastener Length: 5/16", Thread: 6-32, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model:	AN526DD6325
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-151-0549
Schedule B:	7616.10.1000
ECCN:	EAR99



<sup>\*</sup> See page 2 for technical characteristics

# P/N AN526DD632-5 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.250 Inches Minimum And 0.312 Inches Maximum
Fastener Length:	0.281 Inches Minimum And 0.312 Inches Maximum
Head Style:	Button
Head Diameter:	0.303 Inches Minimum And 0.321 Inches Maximum
Head Height:	0.086 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Screw Material:	Aluminum Alloy 2024
Screw Material Document And Classification:	Qq-a-200/3 Fed Spec Single Material Response Or Qq-a-225/6 Fed Spec Single Material Response
Screw Surface Treatment:	Anodize
Screw Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response
Thread Series Designator:	Unc

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/AN526DD632-5">https://military-fasteners.com/screws/machine+screws/AN526DD632-5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.