

## P/N AN530-6R6

## **Description**

diameter: #6 length: 3/8", pan head, type b point, philips recess

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: AN5306R6

Minimum Qty (MOQ): 100

NSN: 5305-00-167-2300

ECCN: EAR99









<sup>\*</sup> See page 2 for technical characteristics

# P/N AN530-6R6 Specifications

Fastener Length:	0.375 Inches Nominal
Head Style:	Round
Head Diameter:	0.240 Inches Minimum And 0.260 Inches Maximum
Head Height:	0.091 Inches Minimum And 0.103 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Features Provided:	Casehardened
Nonmachine Thread Style:	Dog Type (type B Or C)
Nonmachine Nominal Thread Diameter:	0.138 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall Or Zinc Overall

# **How to Order**

Order this tapping screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/tapping+screws/AN530-6R6">https://military-fasteners.com/screws/tapping+screws/AN530-6R6</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/tapping+screws/AN530-6R6">https://military-fasteners.com/screws/tapping+screws/AN530-6R6</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/tapping+screws/AN530-6R6">https://military-fasteners.com/screws/tapping+screws/AN530-6R6</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/tapping+screws/AN530-6R6">https://military-fasteners.com/screws/tapping+screws/AN530-6R6</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/tapping+screws/AN530-6R6">https://military-fasteners.com/screws/tapping+sc