

**Description**

diameter: #6 length: 1/2", pan head - type b point - philips recess

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | AN5306R8         |
| Minimum Qty (MOQ): | 100              |
| NSN:               | 5305-00-167-2301 |



## P/N AN530-6R8 Specifications

|  |  |
|--|--|
| <b>Fastener Length:</b>                      | 0.500 Inches Nominal   |
| <b>Head Diameter:</b>                        | 0.240 Inches Minimum And 0.260 Inches Maximum                |
| <b>Head Height:</b>                          | 0.091 Inches Minimum And 0.103 Inches Maximum                |
| <b>Internal Drive Style:</b>                 | Cross Recess Type 1  |
| <b>Features Provided:</b>                    | Casehardened   |
| <b>Nonmachine Thread Style:</b>              | Dog Type (type B Or C)                                       |
| <b>Nonmachine Nominal Thread Diameter:</b>   | 0.138 Inches   |
| <b>Material:</b>                             | Steel Comp 4130 Overall                                      |
| <b>Material Document And Classification:</b> | An-qq-s-685 Cond N Fed Spec Single Material Response Overall |
| <b>Surface Treatment:</b>                    | Cadmium Overall Or Zinc Overall                              |

## How to Order

Order this tapping screw from our inventory online by visiting <https://military-fasteners.com/screws/tapping+screws/AN530-6R8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.