



Military-Fasteners.com

P/N AN531-8R10

Description

diameter: #8 length: 5/8", 82°, flat head - philips recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN5318R10 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-00-167-2919 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N AN531-8R10 Specifications

| | |
|--|---|
| Fastener Length: | 0.031 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.308 Inches Minimum And 0.332 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Features Provided: | Casehardened |
| Nonmachine Thread Style: | Dog Type (type B Or C) |
| Countersink Angle: | 80.0 Degrees Minimum And 82.0 Degrees Maximum |
| Nonmachine Nominal Thread Diameter: | 0.164 Inches |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |

How to Order

Order this tapping screw from our inventory online by visiting <https://military-fasteners.com/screws/tapping+screws/AN531-8R10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.