

**Description**

Fastener Length: 13/64"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | AN53543                                   |
| Minimum Qty (MOQ):      | 85 EA                                     |
| NSN:                    | 5305-00-253-5614                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N AN535-4-3 Specifications

|   |   |
|---|---|
| <b>Fastener Length:</b>                               | 0.172 Inches Minimum And 0.204 Inches Maximum   |
| <b>Head Style:</b>                                    | Round   |
| <b>Head Diameter:</b>                                 | 0.193 Inches Minimum And 0.211 Inches Maximum   |
| <b>Head Height:</b>                                   | 0.075 Inches Minimum And 0.086 Inches Maximum   |
| <b>Pilot Diameter:</b>                                | 0.092 Inches Minimum And 0.096 Inches Maximum   |
| <b>Pilot Length:</b>                                  | 0.047 Inches Nominal  |
| <b>End Item Identification:</b>                       | W/s:vehicle, Aircraft Refueler R-14; Aircraft, Galaxy C-5; Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130); Support Equipment, B-1 Aircraft; Missile, Air-to-air, Phoenix (aim-54); Torpedo, Mk 48; Missile, All-weather Anti-ship, Harpoon (agm-84); Close In Weapon System (ciws-phalanx); Missile Air-to-air, Sparrow (aim-7); Ground Mobile Force Satellite Comm Term (an/tsc-85a);2320-01-097-0260 Hemtt (heavy Expanded Mobility Tactical Trucks) |
| <b>Features Provided:</b>                             | Casehardened  |
| <b>Nonmachine Thread Style:</b>                       | Drive Screw (type U)  |
| <b>Nonmachine Nominal Thread Diameter:</b>            | 0.114 Inches  |
| <b>Material:</b>                                      | Steel Overall   |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall   |
| <b>Nondefinitive Spec/std Data:</b>                   | U Type  |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN535-4-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.