

**Description**

Fastener Length: 13/64"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN53543
Minimum Qty (MOQ):	85 EA
NSN:	5305-00-253-5614
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N AN535-4-3 Specifications

<b>Fastener Length:</b>	0.172 Inches Minimum And 0.204 Inches Maximum
<b>Head Style:</b>	Round
<b>Head Diameter:</b>	0.193 Inches Minimum And 0.211 Inches Maximum
<b>Head Height:</b>	0.075 Inches Minimum And 0.086 Inches Maximum
<b>Pilot Diameter:</b>	0.092 Inches Minimum And 0.096 Inches Maximum
<b>Pilot Length:</b>	0.047 Inches Nominal
<b>End Item Identification:</b>	W/s:vehicle, Aircraft Refueler R-14; Aircraft, Galaxy C-5; Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130); Support Equipment, B-1 Aircraft; Missile, Air-to-air, Phoenix (aim-54); Torpedo, Mk 48; Missile, All-weather Anti-ship, Harpoon (agm-84); Close In Weapon System (ciws-phalanx); Missile Air-to-air, Sparrow (aim-7); Ground Mobile Force Satellite Comm Term (an/tsc-85a);2320-01-097-0260 Hemtt (heavy Expanded Mobility Tactical Trucks)
<b>Features Provided:</b>	Casehardened
<b>Nonmachine Thread Style:</b>	Drive Screw (type U)
<b>Nonmachine Nominal Thread Diameter:</b>	0.114 Inches
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
<b>Nondefinitive Spec/std Data:</b>	U Type

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN535-4-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.