

Description

Fastener Length: 5/8", Thread: 1/4-28, Head Width: 1/8", Thread Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN565A428H10
Minimum Qty (MOQ):	20 EA
NSN:	5305-00-378-2656
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN565A428H10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Fastener Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Head Style:	Headless (setscrew)
Point Style:	Flat
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.125 Inches Minimum And 0.127 Inches Maximum
Thread Quantity Per Inch:	28
Hardness Rating:	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Material Document And Classification:	Mil-s-7720 Mil Spec 1st Material Response Overall Or Mil-s-18732 Mil Spec 2nd Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/AN565A428H10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.