

P/N AN565A428H16

Description

Fastener Length: 0-63/64", Thread: 1/4-28, Head Width: 1/8", Thread Length: 0-63/64

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: AN565A428H16

Minimum Qty (MOQ): 20

NSN: 5305-00-728-6331

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N AN565A428H16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.985 Inches Minimum And 1.015 Inches Maximum
Fastener Length:	0.985 Inches Minimum And 1.015 Inches Maximum
Head Style:	Headless (setscrew)
Point Style:	Flat
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.125 Inches Nominal
Thread Quantity Per Inch:	28
Hardness Rating:	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Material:	Steel Comp 4032 Overall Or Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/AN565A428H16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/AN565A428H16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/AN565A428H16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/AN565A428H16 and selecting the quantity of the selection of the sele