

# P/N AN565A6H10

### **Description**

Fastener Length: 5/8", Thread: 6-32, Head Width: 1/16", Thread Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model:	ANS65A6H1U
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-814-9935
Schedule B:	7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N AN565A6H10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.625 Inches Maximum
Fastener Length:	0.625 Inches Nominal
Head Style:	Headless (setscrew)
Point Style:	Flat
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.138 Inches
Width Across Flats:	0.062 Inches Minimum And 0.063 Inches Maximum
Thread Quantity Per Inch:	32
Hardness Rating:	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Material:	Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

# **How to Order**

Order this setscrew from our inventory online by visiting <a href="https://military-fasteners.com/screws/setscrews/AN565A6H10">https://military-fasteners.com/screws/setscrews/AN565A6H10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.