

**Description**

Fastener Length: 1/8", Thread: 4-40, Thread Length: 1/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN565AC4L2
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-206-0108
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N AN565AC4L2 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.125 Inches Maximum
<b>Fastener Length:</b>	0.125 Inches Nominal
<b>Head Style:</b>	Headless (setscrew)
<b>Spline Minor Diameter:</b>	0.050 Inches Minimum And 0.051 Inches Maximum
<b>Spline Major Diameter:</b>	0.061 Inches Minimum And 0.062 Inches Maximum
<b>Spline Width:</b>	0.013 Inches Minimum And 0.014 Inches Maximum
<b>Point Style:</b>	Flat
<b>Internal Drive Style:</b>	Six Spline
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Thread Quantity Per Inch:</b>	40
<b>Material Document And Classification:</b>	Mil-s-7720 Mil Spec 1st Material Response Overall Or Mil-s-18732 Mil Spec 2nd Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/AN565AC4L2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.