

## P/N AN565B428H16

### **Description**

Fastener Length: 0-63/64", Thread: 1/4-28, Head Width: 1/8", Thread Length: 0-63/64"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model:	AN565B428H16
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-007-2553
Schedule B:	7318.15.6080
ECCN:	9A991



<sup>\*</sup> See page 2 for technical characteristics

# P/N AN565B428H16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.985 Inches Minimum And 1.015 Inches Maximum
Fastener Length:	0.985 Inches Minimum And 1.015 Inches Maximum
Head Style:	Headless (setscrew)
Point Style:	Cone
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.125 Inches Minimum And 0.127 Inches Maximum
Thread Quantity Per Inch:	28
Hardness Rating:	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Material:	Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

## **How to Order**

Order this setscrew from our inventory online by visiting <a href="https://military-fasteners.com/screws/setscrews/AN565B428H16">https://military-fasteners.com/screws/setscrews/AN565B428H16</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.