

Description

Fastener Length: 3/16", Thread: 6-32, Head Width: 1/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|--------------------|------------------|
| SKU / Model: | AN565B6H3 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5305-01-146-4777 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N AN565B6H3 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 0.178 Inches Minimum And 0.198 Inches Maximum |
| Head Style: | Headless (setscrew) |
| Point Style: | Cone |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.138 Inches |
| Width Across Flats: | 0.0625 Inches Minimum And 0.0635 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Hardness Rating: | 45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall |
| Material: | Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/AN565B6H3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.