



Military-Fasteners.com

P/N AN565C10H6

Description

Fastener Length: 3/8", Thread: 10-24, Head Width: 3/32", Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN565C10H6
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-292-4541
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN565C10H6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Fastener Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Head Style:	Headless (setscrew)
Point Style:	Full Dog
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.094 Inches Minimum And 0.095 Inches Maximum
Features Provided:	Casehardened
Thread Quantity Per Inch:	24
Hardness Rating:	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Material:	Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unc

How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/AN565C10H6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.