

## P/N AN565D1032H9

### **Description**

length: 9/16", thread: 10-32, cup point "

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: AN565D1032H9

Minimum Qty (MOQ): 10

NSN: 5305-00-056-7984

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N AN565D1032H9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.562 Inches Minimum
Fastener Length:	0.562 Inches Nominal
Head Style:	Headless (setscrew)
Point Style:	Cup
Internal Drive Style:	Hexagon
End Item Identification:	Ww/s:aircraft, Viking S-3b; Aircraft, C-2a (reprocured); Aircraft, Hawkeye E-2c; Aircraft, Tomcat F-14; Helicopter, Advance Attack, Ah-1w; Consolidated Targets; F4s Aircraft; Aircraft, C-18a, Ec-18b; Joint Stars Target Radar System
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.094 Inches Minimum And 0.095 Inches Maximum
Thread Quantity Per Inch:	32
Hardness Rating:	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Material:	Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	1 Type And 4 Style

## **How to Order**

Order this setscrew from our inventory online by visiting <a href="https://military-fasteners.com/screws/setscrews/AN565D1032H9">https://military-fasteners.com/screws/setscrews/AN565D1032H9</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.