

Description

Fastener Length: 1/2", Thread: 10-24, Head Width: 3/32", Thread Length: 33/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN565D10H8
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-432-0703
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN565D10H8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.510 Inches Maximum
Fastener Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Head Style:	Headless (setscrew)
Point Style:	Cup
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.0937 Inches Minimum And 0.0947 Inches Maximum
Thread Quantity Per Inch:	24
Hardness Rating:	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Material:	Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	1 Type And 4 Style

How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/AN565D10H8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.