

Description

Thread: 2-56, Thread Length: 1/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN565D2L1 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5305-00-207-2193 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N AN565D2L1 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.072 Inches Maximum |
| Fastener Length: | 0.052 Inches Minimum And 0.072 Inches Maximum |
| Head Style: | Headless (setscrew) |
| Spline Minor Diameter: | 0.037 Inches Minimum And 0.038 Inches Maximum |
| Spline Major Diameter: | 0.049 Inches Minimum And 0.050 Inches Maximum |
| Spline Width: | 0.016 Inches Minimum And 0.017 Inches Maximum |
| Point Style: | Cup |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.086 Inches |
| Thread Quantity Per Inch: | 56 |
| Hardness Rating: | 45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall |
| Material: | Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/AN565D2L1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.