

Description

Fastener Length: 5/16", Thread: 2-56

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN565D2L5
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-351-5334
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN565D2L5 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Fastener Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Head Style:	Headless (setscrew)
Spline Minor Diameter:	0.0375 Inches Minimum And 0.038 Inches Maximum
Spline Major Diameter:	0.049 Inches Minimum And 0.050 Inches Maximum
Spline Width:	0.016 Inches Minimum And 0.017 Inches Maximum
Point Style:	Cup
Internal Drive Style:	Four Spline
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Hardness Rating:	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Minimum Overall
Material:	Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	2 Type And 4 Style

How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/AN565D2L5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.