



★ FASTENERS

Military-Fasteners.com

P/N AN565D4L3

Description

Fastener Length: 3/16", Thread: 4-40, Thread Length: 3/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN565D4L3
Minimum Qty (MOQ):	25
NSN:	5305-00-997-4152
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN565D4L3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Fastener Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Head Style:	Headless (setscrew)
Spline Minor Diameter:	0.050 Inches Minimum And 0.051 Inches Maximum
Spline Major Diameter:	0.061 Inches Minimum And 0.062 Inches Maximum
Spline Width:	0.013 Inches Minimum And 0.014 Inches Maximum
Point Style:	Cup
Internal Drive Style:	Six Spline
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Hardness Rating:	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Material:	Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/AN565D4L3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.