



Military-Fasteners.com

P/N AN565D8H12

Description

Fastener Length: 3/4", Thread: 8-32, Head Width: 5/64", Thread Length: 23/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN565D8H12
Minimum Qty (MOQ):	30 EA
NSN:	5305-00-685-2255
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN565D8H12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.699 Inches Minimum And 0.721 Inches Maximum
Fastener Length:	0.739 Inches Minimum And 0.761 Inches Maximum
Head Style:	Headless (setscrew)
Point Style:	Cup
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.078 Inches Minimum And 0.079 Inches Maximum
Thread Quantity Per Inch:	32
Hardness Rating:	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Material:	Steel Comp 4032 Overall Or Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unc
Specification/standard Data:	88044-an565 Government Standard

How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/AN565D8H12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.