

Description

Fastener Length: 3/4", Thread: 10-32, Head Width: 3/32", Thread Length: 3/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN565DC1032H12
Minimum Qty (MOQ):	25
NSN:	5305-00-247-0521
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N AN565DC1032H12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.739 Inches Minimum And 0.761 Inches Maximum
Fastener Length:	0.739 Inches Minimum And 0.761 Inches Maximum
Head Style:	Headless (setscrew)
Point Style:	Cup
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.0937 Inches Minimum And 0.0947 Inches Maximum
Thread Quantity Per Inch:	32
Hardness Rating:	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Material:	Steel Comp 303 Overall Or Steel Comp 303se Overall
Material Document And Classification:	Astma582 Assn Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unf

How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/AN565DC1032H12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.