

## Description

Fastener Length: 3/4", Thread: 10-32, Head Width: 3/32", Thread Length: 3/4

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	AN565DC1032H12
Minimum Qty (MOQ):	25
NSN:	5305-00-247-0521
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N AN565DC1032H12 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.739 Inches Minimum And 0.761 Inches Maximum
<b>Fastener Length:</b>	0.739 Inches Minimum And 0.761 Inches Maximum
<b>Head Style:</b>	Headless (setscrew)
<b>Point Style:</b>	Cup
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Width Across Flats:</b>	0.0937 Inches Minimum And 0.0947 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Hardness Rating:</b>	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Comp 303 Overall Or Steel Comp 303se Overall
<b>Material Document And Classification:</b>	Astma582 Assn Std All Material Responses Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/AN565DC1032H12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.