

Description

Fastener Length: 1-17/64", Thread: 10-32, Head Width: 3/32", Thread Length: 1-17/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN565DC1032H20
Minimum Qty (MOQ):	25
NSN:	5305-01-046-3893
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN565DC1032H20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.231 Inches Minimum And 1.269 Inches Maximum
Fastener Length:	1.231 Inches Minimum And 1.269 Inches Maximum
Head Style:	Headless (setscrew)
Point Style:	Cup
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.093 Inches Minimum And 0.094 Inches Maximum
Thread Quantity Per Inch:	32
Material:	Steel Comp 303 Overall Or Steel Comp 303se Overall
Material Document And Classification:	Astm A582 Assn Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	1 Type And 4 Style

How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/AN565DC1032H20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.