

## P/N AN565DC2L3

### **Description**

Fastener Length: 3/16", Thread: 2-56, Thread Length: 3/16"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: AN565DC2L3

Minimum Qty (MOQ): 15 EA

NSN: 5305-00-576-6595

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N AN565DC2L3 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.188 Inches Maximum
Fastener Length:	0.188 Inches Nominal
Head Style:	Headless (setscrew)
Spline Minor Diameter:	0.037 Inches Minimum And 0.038 Inches Maximum
Spline Major Diameter:	0.049 Inches Minimum And 0.050 Inches Maximum
Spline Width:	0.016 Inches Minimum And 0.017 Inches Maximum
Point Style:	Cup
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Material:	Steel Comp 303se Overall
Material Document And Classification:	Mil-s-7720 Mil Spec 1st Material Response Overall Or Mil-s-18732 Mil Spec 2nd Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

## **How to Order**

Order this setscrew from our inventory online by visiting <a href="https://military-fasteners.com/screws/setscrews/AN565DC2L3">https://military-fasteners.com/screws/setscrews/AN565DC2L3</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.