

Description


Fastener Length: 3/16", Thread: 4-40, Head Width: 3/64", Thread Length: 3/16", AN565 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN565DC4H3
Minimum Qty (MOQ):	10
NSN:	5305-00-297-4005
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN565DC4H3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.188 Inches Maximum
Fastener Length:	0.188 Inches Nominal
Head Style:	Headless (setscrew)
Point Style:	Cup
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.112 Inches
Width Across Flats:	0.050 Inches Minimum And 0.051 Inches Maximum
Thread Quantity Per Inch:	40
Minimum Yield Strength:	100000 Pounds Per Square Inch
Material:	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 303se Overall Or Steel Comp 316 Overall
Material Document And Classification:	Mil-s-7720 Mil Spec All Material Responses Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 4 Style

How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/AN565DC4H3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.