

**Description**

Fastener Length: 3/16", Thread: 4-40, Head Width: 3/64", Thread Length: 3/16", AN565 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN565DC4H3
Minimum Qty (MOQ):	10
NSN:	5305-00-297-4005
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N AN565DC4H3 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.188 Inches Maximum
<b>Fastener Length:</b>	0.188 Inches Nominal
<b>Head Style:</b>	Headless (setscrew)
<b>Point Style:</b>	Cup
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Width Across Flats:</b>	0.050 Inches Minimum And 0.051 Inches Maximum
<b>Thread Quantity Per Inch:</b>	40
<b>Minimum Yield Strength:</b>	100000 Pounds Per Square Inch
<b>Material:</b>	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 303se Overall Or Steel Comp 316 Overall
<b>Material Document And Classification:</b>	Mil-s-7720 Mil Spec All Material Responses Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Thread Series Designator:</b>	Unc
<b>Nondefinitive Spec/std Data:</b>	3 Type And 4 Style

## How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/AN565DC4H3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.