

Description

Fastener Length: 1/8", Thread: 4-40, Thread Length: 1/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN565DC4L2
Minimum Qty (MOQ):	25 EA
NSN:	5305-00-754-4283
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN565DC4L2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.125 Inches Maximum
Fastener Length:	0.125 Inches Nominal
Head Style:	Headless (setscrew)
Spline Minor Diameter:	0.050 Inches Minimum And 0.051 Inches Maximum
Spline Major Diameter:	0.061 Inches Minimum And 0.062 Inches Maximum
Spline Width:	0.013 Inches Minimum And 0.014 Inches Maximum
Point Style:	Cup
Internal Drive Style:	Six Spline
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Material:	Steel Comp 303 Overall Or Steel Comp 303se Overall
Material Document And Classification:	Mil-s-7720 Mil Spec 1st Material Response Overall Or Mil-s-18732 Mil Spec 2nd Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/AN565DC4L2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.