

Description

Fastener Length: 3/16", Thread: 8-32, Head Width: 5/64", Thread Length: 3/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS51963-34](#)

SKU / Model:	AN565DC8H3
Minimum Qty (MOQ):	25
NSN:	5305-00-297-0142
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN565DC8H3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.188 Inches Maximum
Fastener Length:	0.188 Inches Nominal
Point Style:	Cup
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.078 Inches Minimum And 0.079 Inches Maximum
Features Provided:	Casehardened
Thread Quantity Per Inch:	32
Minimum Yield Strength:	100000 Pounds Per Square Inch
Material:	Steel Comp 302 Overall Or Steel Comp 303 Overall
Material Document And Classification:	Qq-s-763,cl 302 Fed Spec 1st Material Response Overall Or Qq-s-763,cl 303 Fed Spec 2nd Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unc

How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/AN565DC8H3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.