

P/N AN565E624H14

Description

Setscrew part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: AN565E624H14

Minimum Qty (MOQ): 15 EA

NSN: 5305-00-559-9072

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N AN565E624H14 Specifications

| Thread Class: | 3a |
|--|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.875 Inches Maximum |
| Fastener Length: | 0.875 Inches Nominal |
| Head Style: | Headless (setscrew) |
| Point Style: | Half Dog |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.375 Inches |
| Width Across Flats: | 0.187 Inches Minimum And 0.189 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Hardness Rating: | 45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall |
| lii Part Name Assigned By Controlling Agency: | Navy Special Project |
| Material: | Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unf |

How to Order

Order this setscrew from our inventory online by visiting https://military-fasteners.com/screws/setscrews/AN565E624H14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.