

Description

Fastener Length: 1-17/64", Thread: 1/4-28, Head Width: 1/8", Thread Length: 1-17/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN565F428H20
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-038-4759
Schedule B:	7318.15.8020
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN565F428H20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.231 Inches Minimum And 1.269 Inches Maximum
Fastener Length:	1.231 Inches Minimum And 1.269 Inches Maximum
Head Style:	Headless (setscrew)
Point Style:	Oval
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.125 Inches Minimum And 0.127 Inches Maximum
Thread Quantity Per Inch:	28
Hardness Rating:	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Material:	Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	1 Type And 3 Style
Departure From Cited Document:	As Modified By Material

How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/AN565F428H20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.