

P/N AN565F428H9

Description

Fastener Length: 9/16", Thread: 1/4-28, Head Width: 1/8", Thread Length: 9/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: AN565F428H9

Minimum Qty (MOQ): 15 EA

NSN: 5305-01-006-8979

Schedule B: 7318.15.8020

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N AN565F428H9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.552 Inches Minimum And 0.572 Inches Maximum
Fastener Length:	0.552 Inches Minimum And 0.572 Inches Maximum
Head Style:	Headless (setscrew)
Point Style:	Oval
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.125 Inches Minimum And 0.127 Inches Maximum
Thread Quantity Per Inch:	28
Hardness Rating:	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Material:	Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	1 Type And 3 Style

How to Order

Order this setscrew from our inventory online by visiting https://military-fasteners.com/screws/setscrews/AN565F428H9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.