

Description

Fastener Length: 0-1/1", Thread: 8-32, Head Width: 5/64", Thread Length: 0-1/1"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN565F8H16 |
| Minimum Qty (MOQ): | 30 EA |
| NSN: | 5305-00-402-8840 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N AN565F8H16 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.985 Inches Minimum And 1.015 Inches Maximum |
| Fastener Length: | 0.985 Inches Minimum And 1.015 Inches Maximum |
| Head Style: | Headless (setscrew) |
| Point Style: | Oval |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.164 Inches |
| Width Across Flats: | 0.078 Inches Minimum And 0.079 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Hardness Rating: | 45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall |
| Material: | Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,c1 3 Fed Spec All Treatment Responses Overall |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 1 Type And 3 Style |

How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/AN565F8H16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.