

**Description**

Fastener Length: 3/4", Thread: 6-32, Head Width: 1/16", Thread Length: 3/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN565FC6H12
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-459-9886
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N AN565FC6H12 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.739 Inches Minimum And 0.761 Inches Maximum
<b>Fastener Length:</b>	0.739 Inches Minimum And 0.761 Inches Maximum
<b>Head Style:</b>	Headless (setscrew)
<b>Point Style:</b>	Oval
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Width Across Flats:</b>	0.063 Inches Minimum And 0.064 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Material:</b>	Steel Comp 303se Overall
<b>Material Document And Classification:</b>	Astm A582 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unc
<b>Nondefinitive Spec/std Data:</b>	1 Type And 3 Style

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN565FC6H12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.