

Description

Fastener Length: 1-7/8", Thread: 1/4-24, Thread Length: 37/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN5C16A |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-00-180-1925 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N AN5C16A Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.500 Inches Minimum And 0.578 Inches Maximum |
| Fastener Length: | 1.828 Inches Minimum And 1.875 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.172 Inches Minimum And 0.204 Inches Maximum |
| Width Between Flats: | 0.490 Inches Minimum And 0.502 Inches Maximum |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 1.297 Inches Minimum And 1.328 Inches Maximum |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Material: | Steel Comp 431 Overall |
| Material Document And Classification: | Mil-s-18732 Mil Spec Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unf |

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN5C16A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.